Index to

EXPERIMENTAL MECHANICS

Volume 42, 2002

TITLE INDEX

A New Interferometric Method for Vibration Measurement by Electronic Holography—D. Borza, 432–438 (Dec.).

A New Microtensile Tester for the Study of MEMS Materials with the Aid of Atomic Force Microscopy—I. Chasiotis, W. G. Knauss, 51–57 (Mar.).

A Parametric Study of Laser-Induced Thin Film Spallation—J. Wang, R. L. Weaver and N. R. Sottos, 74–83 (Mar.).

A Shear-Compression Specimen for Large Strain Testing—D. Rittel, S. Lee and G. Ravichandran, 58–64 (Mar.).

A Simple Technique for Determining Yield Strenght of Thin Films—M. H. Gordon, W. F. Schmidt, Q. Qiao, B. Huang and S. S. Ang, 232–236 (Sept.).

A Technique to Measure Fatigue Crack Growth Threshold—K. E. Goecke, M. A. Moshier, 182–185 (June).

A Tension Split Hopkinson Bar for Investigating the Dynamic Behavior of Sheet Metals—H. Huh, W. J. Kang and S. S. Han, 8–17 (Mar.).

Analysis of a Multiaxial Test on a C/C Composite by Using Digital Image Correlation and a Damage Model—J.-P. Perie, S. Calloch, C. Cluzel and F. Hild, 318–328 (Sept.).

Application of the Fourier Transform in Electronic Speckle Photography—Z. Yuanpeng, Z. Huaning, Z. Wenling and L. Hefei, 18–24 (Mar.).

Automated Imaging to Track the 3D Motion of Particles—I. Govender, M. S. Powell and G. N. Nurick, 153–160 (June).

Characterization of Interfacial Failure Using a Reflected Light Technique—V. T. Bechel, G. P. Tandon, 200–205 (June).

Characterization of Short Duration Stress Pulses Generated by Impacting Laminated Carbon-Fiber/Epoxy Composites with Magnetic Flyer Plates—H. A. Bruck, D. Casem, R. L. Williamson and J. S. Epstein, 279–287 (Sept.).

Circumferential Strain Measurement for a Concrete Cylinder in Uniaxial Compression by a Fiber Optic Sensor—Q. Li, F. Ansari, 37–42 (Mar.).

Computational Method for the SPSD of Dynamic Systems and its Application—Z. WenLi, L. DeGang, 295–297 (Sept.).

Computer-Aided Photoelasticity by an Optimum Phase Stepping Method—S. Barone, G. Burriesci and G. Petrucci, 132–139 (June).

Coupled Experiments and Simulations of Microstructural Damage in Wood—E. N. Landis, S. Vasic, W. G. Davids and P. Parrod, 389–394 (Dec.).

Crack Linkup—L. Ma, A. S. Kobayashi, S. N. Atluri and P. W. Tan, 147–152 (June.).

Degradation of Nylon-6/Clay Nanocomposites in NOx—J. S. Shelley, K. L. DeVries, 178–181 (June).

Delamination of a High-Temperature Sandwich Plate—K. M. Liechti, B. Marton, 206–213 (June).

Determination of Impact Parameters by Optical Measurement of the Impactor Displacement—J. Degrieck and P. Verleysen, 298–302 (Sept.).

Digital Volume Correlation Including Rotational Degrees of Freedom During Minimalization—T. S. Smith, B. K. Bay and M. M. Rashid, 272–278 (Sept.).

Distributed Strain Sensing Using Frequency-Modulated Continuous-Wave Reflectometric Optical Technique—L. Seah, P. C. Won, 288–294 (Sept.).

Dynamic Fiber Debonding and Frictional Push-out in Model Composite Systems: Experimental Observations—Zhouhua Li, Xiaopeng Bi, John Lambros, and Philippe H. Geubelle

Dynamic Shearing Resistance of Molten Metal Films Under High Pressures and Extremely High Shearing Rates–M. Okada, N.-S. Liou and V. Prakash, 161–171 (June).

Dynamic Stress Chain Formation in a Two-Dimensional Particle Bed—K. M. Roessig, J. C. Foster and S. G. Bardenhagen, 329–337 (Sept.).

Effects of Boundary Conditions and Anisotropy on Elastically Bent Silicon—S. K. Kaldor, I. C. Noyan, 353–358 (Sept.).

Elasto-Optic Technique for Measurement of Elastic Wave Propagation in Solids—B. K. Henderson, K. I. Maslov, G. Eggenspieler and V. K. Kinra, 338–343 (Sept.).

Epoxy-Based Electroactive Polymer Gels—Y. Yoshioka, P. Calvert, 404–408 (Dec.).

Evaluating the Mechanical Behavior of Arterial Tissue Using Digital Image Correlation—D. Zhang, C. D. Eggleton and D. Arola, 409–416 (Dec.).

Experimental Evidence of Parasitic Effects in the Shear Test on Sandwich Beams—M. Grediac, L. Dufort, 186–193 (June).

Experimental Full Field Investigations of Resonant Vibrations for Piezoceramic Plates by an Optical Interferometry Method—C.-C. Ma, C.-H. Huang, 140–146 (June).

Experimental Investigation of Structural Response to Generalized Ground Shock Excitations—Y. Lu, H. Hao and G. Ma, 261–271 (Sept.).

Experimental Mechanics Individual Paper Directory 1971—214–215 (June).

Fabric Thickness Dynamic Measurement during a Classic Uniaxial Tensile Test—S. Fontaine, B. Durand and J. M. Freyburger, 84–92 (Mar.).

Fatigue and Fracture of Bovine Dentin—D. Arola, J. A. Rouland and D. Zhang, 380–388 (Dec.).

Flexural Fatigue Behavior of Threaded Connections for Large Diameter Pipes—A. H. Varma, A. K. Salecha, B. Wallace and B. W. Russell, 1–7 (Mar.).

Fracture Testing of A Self-Healing Polymer Composite—E. Brown, N. R. Sottos and S. R.White, 372–379 (Dec.).

Full-Field Speckle Pattern Image Correlation with B-Spline Deformation Function—P. Cheng, M. A. Sutton, H. Schreier and S. R. McNeill, 344–352 (Sept.).

Guest Editorial—H. Bruck, 359–360 (Dec.).

Heating During Shearing and Opening Dominated Dynamic Fracture of Polymers—T. Bjerke, J. Lambros, 107–114 (Mar.).

High-Strain-Rate Compressive Behavior of a Rigid Polyurethane Foam with Various Densities—W. W. Chen, F. Lu and N. Winfree, 65–73 (Mar.).

Indentation Failure in Composite Sandwich Structures—E. E. Gdoutos, I. Daniel and K.-A. Wang, 426–431 (Dec.).

In-Situ Tensile Testing of Nano-Scale Specimens in SEM and TEM—M. A. Haque, M. T. A. Saif, 123–128 (Mar.).

Investigation of Shrinkage-Induced Stresses in Stereolithography Photo-Curable Resins—D. Karalekas, D. Rapti, E. E. Gdoutos and A. Aggelopoulos, 439–444 (Dec.).

Moire-Numerical Hybrid Analysis of Cracks in Orthotropic Media—J. Rhee, R. E. Rowlands, 311–317 (Sept.).

Multiple Force Identification for Complex Structures—R. Adams, J. F. Doyle, 25–36 (Mar.).

Novel Load Cell for Measuring Axial Force, Shear Force, and Bending Movement in Large-Scale Structural Experiments—A. Blakeborough, D. Clément, M. S. Williams and A. Woodward, 115–122 (Mar.).
On Testing of Charpy Specimens Using the One-Point Bend Impact Technique—D. Rittel, A. Pineau, J. Clisson and L. Rota, 247–252 (Sept.).
Optoelectronic Strain Measurement for Flywheels—R. P. Emerson, C. E. Bakis, 237–246 (Sept.).
Pulse Shaping Techniques for Testing Brittle Materials with a Split Hopkinson Pressure Bar—D. J. Frew, M. J. Forrestal and W. Chen, 93–106 (Mar.).
Rigid Biological Composite Materials—G. Mayer, M. Sarikaya, 395–403 (Dec.).
Systematic Errors in Digital Image Correlation Due to Undermatched Subset Shape Functions—H. Schreier, M. A. Sutton, 303–310 (Sept.).
Test Method for Measuring Strength of a Curved Sandwich Beam—A. M. Layne, L. A. Carlsson, 194–199 (June).
The Effect of Sabot Mass on the Striker Bar for Split Hopkinson Pressure Bar Experiments—M. J. Forrestal, D. J. Frew and W. W. Chen, 129–131 (June).
The Role of Mechanics in Biological and Biologically-Inspired Materials—H. Bruck, J. J. Evans and M. Peterson, 361–371 (Dec.).
The Use of Automated Projection Interferometry in Monitoring Aerofoil Buckling—C. A. Featherston, W. D. Lester, 253–260 (Sept.).
The Use of Phase-Stepping for the Measurement of Characteristic Parameters in Integrated Photoelasticity—R. Tomlinson, E. A. Patterson, 43–50 (Mar.).
Viscoelasticity—A. M. Korol, J. R. Valverde and R. J. Rasia, 172–177 (June).

AUTHOR INDEX

Adams, D. F.—Development of an Electromechanical Triaxial Test Facility for Composite Materials, 312-320 (Sept.).
Adams, R.—Multiple Force Identification for Complex Structures, 25–36, (Mar.).
Aggelopoulos, A.—Investigation of Shrinkage-Induced Stresses in Stereolithography Photo-Curable Resins, 439–444 (Dec.).
Ang, S.S.—A Simple Technique for Determining Yield Strenght of Thin Films, 232–236, (Sept.).
Ansari, F.—Circumferential Strain Measurement for a Concrete Cylinder in Uniaxial Compression by a Fiberoptic Sensor, 37–42, (Mar.).
Arola, D.—Evaluating the Mechanical Behavior of Arterial Tissue Using Digital Image Correlation, 409–416 (Dec.).
Arola, D.—Fatigue and Fracture of Bovine Dentin, 380–388 (Dec.).
Atluri, S. N.—Crack Linkup: An Experimental Analysis, 147–152, (June).
Bakis, C. E.—Optoelectronic Strain Measurement for Flywheels, 237–246, (Sept.).
Bardenhagen S. G.—Dynamic Stress Chain Formation in a Two-Dimensional Particle Bed, 329–337, (June).
Barone, S.—Computer-Aided Photoelasticity by an Optimum Phase Stepping Method, 132–139, (June).
Bay, B. K.—Digital Volume Correlation Including Rotational Degrees of Freedom During Minimalization, 272–278, (Sept.).
Bechel, V. T.—Characterization of Interfacial Failure Using a Reflected Light Technique, 200–205, (June).
Bi, Xiaopeng—Dynamic Fiber Debonding and Frictional Push-out in Model Composite Systems: Experimental Observations, 417–425 (Dec.).
Bjerke, T.—Heating During Shearing and Opening Dominated Dynamic Fracture of Polymers, 107–114, (Mar.).
Blakeborough, A.—Novel Load Cell for Measuring Axial Force, Shear Force, and Bending Movement in Large-Scale Structural Experiments, 115–122, (Mar.).
Borza, D.—A New Interferometric Method for Vibration Measurement by Electronic Holography, 432–438 (Dec.).
Brown, E.—Fracture Testing of A Self-Healing Polymer Composite, 372–379 (Dec.).
Bruck, H. A.—Characterization of Short Duration Stress Pulses Generated by Impacting Laminated Carbon-Fiber/Epoxy Composites with Magnetic Flyer Plates, 279–287, (Sept.).
Bruck, H.—Guest Editorial: Biological and Biologically-Inspired Materials, 359–360 (Dec.).
Bruck, H.—The Role of Mechanics in Biological and Biologically-Inspired Materials, 361–371 (Dec.).
Burriesci, G.—Computer-Aided Photoelasticity by an Optimum Phase Stepping Method, 132–139, (June).
Calloch, S.—Analysis of a Multiaxial Test on a C/C Composite by Using Digital Image Correlation and a Damage Model, 318–328, (Sept.).
Calvert, P.—Rigid Biological Composite Materials: Structural Examples for Biomimetic Design, 404–408 (Dec.).
Casem, D.—Characterization of Short Duration Stress Pulses Generated by Impacting Laminated Carbon-Fiber/Epoxy Composites with Magnetic Flyer Plates, 279–287, (Sept.).
Chasiotis, I.—A New Microtensile Tester for the Study of MEMS Materials with the Aid of Atomic Force Microscopy, 51–57, (Mar.).
Chen, W.—Pulse Shaping Techniques for Testing Brittle Materials with a Split Hopkinson Pressure Bar, 93–106, (Mar.).
Chen, W. W.—High-Strain-Rate Compressive Behavior of a Rigid Polyurethane Foam with Various Densities, 65–73, (Mar.).
Chen, W. W.—The Effect of Sabot Mass on the Striker Bar for Split Hopkinson Pressure Bar Experiments, 129–131, (June).
Cheng, P.—Full-Field Speckle Pattern Image Correlation with B-Spline Deformation Function, 344–352, (Sept.).
Clément, D.—Novel Load Cell for Measuring Axial Force, Shear Force, and Bending Movement in Large-Scale Structural Experiments, 115–122, (Mar.).
Clisson, J.—On Testing of Charpy Specimens Using the One-Point Bend Impact Technique, 247–252, (Sept.).
Cluzel, C.—Analysis of a Multiaxial Test on a C/C Composite by Using Digital Image Correlation and a Damage Model, 318–328, (Sept.).
Daniel, I.—Indentation Failure in Composite Sandwich Structures, 426–431 (Dec.).
Davids, W. G.—Coupled Experiments and Simulations of Microstructural Damage In Wood, 389–394 (Dec.).
DeGang, L.—Computational Method for the SPSD of Dynamic Systems and its Application, 295–297, (Sept.).
Degrieck, J.—Determination of Impact Parameters by Optical Measurement of the Imapactor Displacement, 298–302, (Sept.).
DeVries, K. L.—Degradation of Nylon-6/Clay Nanocomposites in NOx, 178–181, (Sept.).
Doyle, J. F.—Multiple Force Identification for Complex Structures, 25–36, (Mar.).
Dufort, L.—Experimental Evidence of Parasitic Effects in the Shear Test on Sandwich Beams, 186–193, (June).
Durand B.—Fabric Thickness Dynamic Measurement during a Classic Uniaxial Tensile Test, 84–92, (Mar.).
Eggenspieler, G.—Elasto-Optic Technique for Measurement of Elastic Wave Propagation in Solids, 338–343, (Sept.).
Eggleton, C. D.—Evaluating the Mechanical Behavior of Arterial Tissue Using Digital Image Correlation, 409–416 (Dec.).
Emerson, R. P.—Optoelectronic Strain Measurement for Flywheels, 237–246, (Sept.).
Epstein, J. S.—Characterization of Short Duration Stress Pulses Generated by Impacting Laminated Carbon-Fiber/Epoxy Composites with Magnetic Flyer Plates, 279–287, (Sept.).
Evans, J. J.—The Role of Mechanics in Biological and Biologically Inspired Materials, 361–371 (Dec.).
Experimental Mechanics Individual Paper Directory 1971, 214–215, (June).
Featherston, C. A.—The Use of Automated Projection Interferometry in Monitoring Aerofoil Buckling, 253–260, (Sept.).
Fontaine, S.—Fabric Thickness Dynamic Measurement During a Classic Uniaxial Tensile Test, 84–92, (Mar.).
Forrestal, M. J.—Pulse Shaping Techniques for Testing Brittle Materials with a Split Hopkinson Pressure Bar, 93–106, (Mar.).
Forrestal, M. J.—The Effect of Sabot Mass on the Striker Bar for Split Hopkinson Pressure Bar Experiments, 129–131, (June).
Foster, J. C.—Dynamic Stress Chain Formation in a Two-Dimensional Particle Bed, 329–337, (Sept.).

Frew, D. J.—Pulse Shaping Techniques for Testing Brittle Materials with a Split Hopkinson Pressure Bar, 93–106, (Mar.).
Frew, D. J.—The Effect of Sabot Mass on the Striker Bar for Split Hopkinson Pressure Bar Experiments, 129–131, (June).
Gdoutos, E. E.—Investigation of Shrinkage Induced Stresses in Stereolithography Photo-Curable Resins, 439–444 (Dec.).
Gdoutos, E. E.—Indentation Failure in Composite Sandwich Structures, 426–431 (Dec.).
Geubelle, Philippe H.—Dynamic Fiber Debonding and Frictional Push-out in Model Composite Systems: Experimental Observations, 417–425 (Dec.).
Goecke, K. E.—A Technique to Measure Fatigue Crack Growth Threshold, 182–185, (June).
Gordon, M. H.—A Simple Technique for Determining Yield Strenght of Thin Films, 232–236, (Sept.).
Govender, I.—Automated Imaging to Track the 3D Motion of Particles, 153–160, (June).
Grediac, M.—Experimental Evidence of Parasitic Effects in the Shear Test on Sandwich Beams, 186–193, (June).
Han, S. S.—A Tension Split Hopkinson Bar for Investigating the Dynamic Behavior of Sheet Metals, 8–17, (Mar.).
Hao, H.—Experimental Investigation of Structural Response to Generalized Ground Shock Excitations, 261–271, (Sept.).
Haque, M. A.–In-situ tensile testing of nano-scale specimens in SEM and TEM, 123–128, (Mar.).
Hefei, L.—Application of the Fourier Transform in Electronic Speckle Photography, 18–24, (Mar.).
Henderson, B. K.—Elasto-Optic Technique for Measurement of Elastic Wave Propagation in Solids, 338–343, (Sept.).
Hild, F.—Analysis of a Multiaxial Test on a C/C Composite by Using Digital Image Correlation and a Damage Model, 318–328, (Sept.).
Huang, B.—A Simple Technique for Determining Yield Strenght of Thin Films, 232–236, (Sept.).
Huang, C.-H.—Experimental Full Field Investigations of Resonant Vibrations for Piezoceramic Plates by an Optical Interferometry Method, 140–146, (June).
Huaning, Z.—Application of the Fourier Transform in Electronic Speckle Photography, 18–24, (Mar.).
Huh, H.—A Tension Split Hopkinson Bar for Investigating the Dynamic Behavior of Sheet Metals, 8–17, (Mar.).
Kaldor, S. K.– Effects of Boundary Conditions and Anisotropy on Elastically Bent Silicon, 353–358, (Sept.).
Kang, W. J.—A Tension Split Hopkinson Bar for Investigating the Dynamic Behavior of Sheet Metals, 8–17, (Mar.).
Karalekas, D.—Investigation of Shrinkage-Induced Stresses in Stereolithography Photo-Curable Resins, 439–444 (Dec.).
Kinra, V. K.—Elasto-Optic Technique for Measurement of Elastic Wave Propagation in Solids, 338–343, (Sept.).
Knauss, W. G.—A New Microtensile Tester for the Study of MEMS Materials with the Aid of Atomic Force Microscopy, 51–57, (Mar.).
Kobayashi, A. S.—Crack Linkup: An Experimental Analysis, 147–152, (June).
Korol, A. M.—Viscoelasticity: Fractal Parameters Studied on Mammalian Erythrocytes Under Shear Stress, 172–177, (June).
Lambros, J.—Dynamic Fiber Debonding and Frictional Push-out in Model Composite Systems: Experimental Observations, 417–425 (Dec.).
Lambros, J.—Heating During Shearing and Opening Dominated Dynamic Fracture of Polymers, 107–114, (Mar.).
Landis, E. N.—Coupled Experiments and Simulations of Microstructural Damage In Wood, 389–394 (Dec.).
Layne, A. M.—Test Method for Measuring Strength of a Curved Sandwich Beam, 194–199, (June).
Lee, S.—A Shear-Compression Specimen for Large Strain Testing, 58–64, (Mar.).
Leif, A. C.—Test Method for Measuring Strength of a Curved Sandwich Beam, 194–199, (June).
Li, Q.—Circumferential Strain Measurement for a Concrete Cylinder in Uniaxial Compression by a Fiberoptic Sensor, 37–42, (Mar.).
Li, Z.—Dynamic Fiber Debonding and Frictional Push-out in Model Composite Systems: Experimental Observations, 417–425 (Dec.).
Liechti, K. M.—Delamination of a High-Temperature Sandwich Plate, 206–213, (June).
Liou, N.-S.—Dynamic Shearing Resistance of Molten Metal Films Under High Pressures and Extremely High Shearing Rates, 161–171, (June).
Lu, F.—High-Strain-Rate Compressive Behavior of a Rigid Polyurethane Foam with Various Densities, 65–73, (Mar.).
Lu, Y.—Experimental Investigation of Structural Response to Generalized Ground Shock Excitations, 261–271, (Sept.).
Ma, C.-C.—Experimental Full Field Investigations of Resonant Vibrations for Piezoceramic Plates by an Optical Interferometry Method, 140–146, (Sept.).
Ma, G.—Experimental Investigation of Structural Response to Generalized Ground Shock Excitations, 261–271, (Sept.).
Ma, L.—Crack Linkup: An Experimental Analysis, 147–152, (Sept.).
Marton, B.—Delamination of a High-Temperature Sandwich Plate, 206–213, (Sept.).
Maslov, K. I.—Elasto-Optic Technique for Measurement of Elastic Wave Propagation in Solids, 338–343, (Sept.).
Mayer, G.—Rigid Biological Composite Materials: Structural Examples for Biomimetic Design, 395–403 (Dec.).
McNeill, S. R.—Full-Field Speckle Pattern Image Correlation with B-Spline Deformation Function, 344–352, (Sept.).
Moshier, M. A.—A Technique to Measure Fatigue Crack Growth Threshold, 182–185, (Sept.).
Noyan, I. C.—Effects of Boundary Conditions and Anisotropy on Elastically Bent Silicon, 353–358, (Sept.).
Nurick, G. N.—Automated Imaging to Track the 3D Motion of Particles, 153–160, (Sept.).
Okada, M.—Dynamic Shearing Resistance of Molten Metal Films Under High Pressures and Extremely High Shearing Rates, 161–171, (June).
Patterson, E. A.—The Use of Phase-Stepping for the Measurement of Characteristic Parameters in Integrated Photoelasticity, 43–50, (Mar.).
Perie, J.-P.—Analysis of a Multiaxial Test on a C/C Composite by Using Digital Image Correlation and a Damage Model, 318–328, (Sept.).
Peterson, M.—The Role of Mechanics in Biological and Biologically Inspired Materials, 361–371 (Dec.).
Petrucci, G.—Computer-Aided Photoelasticity by an Optimum Phase Stepping Method, 132–139, (June).
Pineau, A.—On Testing of Charpy Specimens Using the One-Point Bend Impact Technique, 247–252, (Sept.).
Powell, M. S.—Automated Imaging to Track the 3D Motion of Particles, 153–160, (June).
Prakash, V.—Dynamic Shearing Resistance of Molten Metal Films Under High Pressures and Extremely High Shearing Rates, 161–171, (June).
Qiao, Q.—A Simple Technique for Determining Yield Strength of Thin Films, 232–236, (Sept.).
Rapti, D.—Investigation of Shrinkage Induced Stresses in Stereolithography Photo-Curable Resins, 439–444 (Dec.).
Rashid, M. M.—Digital Volume Correlation Including Rotational Degrees of Freedom During Minimalization, 272–278, (Sept.).
Rasia, R. J.—Viscoelasticity: Fractal Parameters Studied on Mammalian Erythrocytes Under Shear Stress, 172–177, (June).
Ravichandran, G.—A Shear-Compression Specimen for Large Strain Testing, 58–64, (Mar.).
Rhee, J.—Moire-Numerical Hybrid Analysis of Cracks in Orthotropic Media, 311–317, (Sept.).
Rittel, D.—A Shear-Compression Specimen for Large Strain Testing, 58–64, (Mar.).
Rittel, D.—On Testing of Charpy Specimens Using the One-Point Bend Impact Technique, 247–252, (Sept.).
Roessig, K. M.—Dynamic Stress Chain Formation in a Two-Dimensional Particle Bed, 329–337, (Sept.).
Rota, L.—On Testing of Charpy Specimens Using the One-Point Bend Impact Technique, 247–252, (Sept.).
Rouland J. A.—Fatigue and Fracture of Bovine Dentin, 380–388 (Dec.).
Rowlands, R. E.—Moire-Numerical Hybrid Analysis of Cracks in Orthotropic Media, 311–317, (Sept.).
Russell, B. W.—Flexural Fatigue Behavior of Threaded Connections for Large Diameter Pipes, 1–7, (Mar.).
Saif, M. T. A.—In-Situ Tensile Testing of Nano-Scale Specimens in SEM and TEM, 123–128, (Mar.).

Salecha, A. K.—Flexural Fatigue Behavior of Threaded Connections for Large Diameter Pipes, 1–7, (Mar.).
Sarikaya, M.—Rigid Biological Composite Materials: Structural Examples for Biomimetic Design, 395–403 (Dec.).
Schmidt, W. F.—A Simple Technique for Determining Yield Strength of Thin Films, 232–236, (Sept.).
Schreier, H.—Full-Field Speckle Pattern Image Correlation with B-Spline Deformation Function, 344–352, (Sept.).
Schreier, H.—Systematic Errors in Digital Image Correlation Due to Undermatched Subset Shape Functions, 303–310, (Sept.).
Seah, L.—Distributed Strain Sensing Using Frequency-Modulated Continuous-Wave Reflectometric Optical Technique, 288–294, (Sept.).
Shelley, J. S.—Degradation of Nylon-6/Clay Nanocomposites in NOx, 178–181, (June).
Smith, T. S.—Digital Volume Correlation Including Rotational Degrees of Freedom During Minimalization, 272–278, (Sept.).
Sottos, N. R.—Fracture Testing of A Self-Healing Polymer Composite, 372–379 (Dec.).
Sottos, N. R.—A Parametric Study of Laser-Induced Thin Film Spallation, 74–83, (Mar.).
Sutton, M. A.—Full-Field Speckle Pattern Image Correlation with B-Spline Deformation Function, 344–352, (Sept.).
Sutton, M. A.—Systematic Errors in Digital Image Correlation Due to Undermatched Subset Shape Functions, 303–310, (Sept.).
Tan, P. W.—Crack Linkup: An Experimental Analysis, 147–152, (June).
Tandon, G. P.—Characterization of Interfacial Failure Using a Reflected Light Technique, 200—205, (June).
Tomlinson, R.—The Use of Phase-Stepping for the Measurement of Characteristic Parameters in Integrated Photoelasticity, 43–50, (Mar.).
Valverde, J. R.—Viscoelasticity: Fractal Parameters Studied on Mammalian Erythrocytes Under Shear Stress, 172–177, (June).
Varma, A. H.—Flexural Fatigue Behavior of Threaded Connections for Large Diameter Pipes, 1–7, (Mar.).
Vasic, S.—Coupled Experiments and Simulations of Microstructural Damage In Wood, 389–394 (Dec.).
Verleysen, P.—Determination of Impact Parameters by Optical Measurement of the Impactor Displacement, 298–302, (Sept.).
Wallace, B.—Flexural Fatigue Behavior of Threaded Connections for Large Diameter Pipes, 1–7, (Mar.).
Wang, J.—A Parametric Study of Laser-Induced Thin Film Spallation, 74–83, (Mar.).
Wang, K.-A.— Indentation Failure in Composite Sandwich Structures, 426–431 (Dec.).
Weaver, Richard L. — A Parametric Study of Laser-Induced Thin Film Spallation, 74–83, (Mar.).
WenLi, Z.—Computational Method for the SPSD of Dynamic Systems and its Application, 295–297, (Sept.).
Wenling, Z.—Application of the Fourier Transform in Electronic Speckle Photography, 18–24, (Mar.).
White, S. R.—Fracture Testing of a Self-Healing Polymer Composite, 372–379 (Dec.).
Williams, M. S.—Novel Load Cell for Measuring Axial Force, Shear Force, and Bending Movement in Large-Scale Structural Experiments, 115–122, (Mar.).
Williamson, R.L.—Characterization of Short Duration Stress Pulses Generated by Impacting Laminated Carbon-Fiber/Epoxy Composites with Magnetic Flyer Plates, 279–287, (Sept.).
Winfree, N.—High-Strain-Rate Compressive Behavior of a Rigid Polyurethane Foam with Various Densities, 65–73, (Mar.).
Won, P. C.—Distributed Strain Sensing Using Frequency-Modulated Continuous-Wave Reflectometric Optical Technique, 288–294, (Sept.).
Woodward, A.–Novel Load Cell for Measuring Axial Force, Shear Force, and Bending Movement in Large-Scale Structural Experiments, 115–122, (Mar.).
Yoshioka, Y.—Epoxy-Based Electroactive Polymer Gels, 404–408 (Dec.).
Yuanpeng, Z.—Application of the Fourier Transform in Electronic Speckle Photography, 18–24, (Mar.).
Zhang, D.—Evaluating the Mechanical Behavior of Arterial Tissue Using Digital Image Correlation, 409–416 (Dec.).
Zhang, D.—Fatigue and Fracture of Bovine Dentin, 380–388 (Dec.).